

| | |
|----------------------|---------------------|
| Capacity (L.) | 225 |
| Stave thickness (mm) | 22 |
| Galvanised hoops | 6 |
| Chestnut wood hoops | 4 |
| Weight (kg) | 40 |
| Height (cm) | 95 |
| Ø chime (cm) | 56,5 |
| Ø bilge (cm) | 69 |
| Interior surface | 2,02 m ² |
| Riveted hoops | yes |

TYPE OF OAK

Quercus Sessilis & Quercus Robur
Selection and assembly of numerous french sources
Naturally seasoned in the open air for a minimum of 20 to 24 months
Checked for the absence of contaminants

CERTIFICATION/ACCREDITATION

100% PEFC

We are fully committed to the sustainable development of forests and Bureau Veritas certifies our supplies from PEFC forests and unquestioned sourcing. Bureau Veritas certifies that Tonnellerie Bernard respects the criteria for the certification of the control chain (BVFR-PEFC-COC -2172175-G).

PACKAGING

Unique identification number
Transport wrapping - Cardboard end protections / bubble paper / cling wrap

MANUFACTURE

| | |
|--------------------------------|---|
| Traditional wood fire toasting | Light (L), Medium (M), Medium+ (M+), Heavy (H) |
| Bung hole | Cauterized - Diameter 48/52 |
| Heads | Blend of oak + stainless steel pins + natural fixations |
| Watertightness testing | High pressure hot water |
| Options | Toasted heads Hoops painted black Special laser engraving Spigot hole Wooden or silicone bung |

