

Capacity (L.)	225
Stave thickness (mm)	22
Galvanised hoops	8
Chestnut wood hoops	no
Weight (kg)	40
Height (cm)	95
Ø chime (cm)	56,5
Ø bilge (cm)	69
Interior surface	2,02 m ²
Riveted hoops	yes

TYPE OF OAK

Quercus Sessilis & Quercus Robur
Selection and assembly of numerous french sources
Naturally seasoned in the open air for a minimum of 20 to 24 months
Checked for the absence of contaminants

CERTIFICATION/ACCREDITATION

100% PEFC
Nous nous engageons dans le programme de la gestion durable des forêts (PEFC) et Bureau Veritas Certification certifie que la Tonnellerie Bernard respecte les critères définis pour la certification de la chaîne de contrôle (BVFR-PEFC-COC -2172175-G).

PACKAGING

Unique identification number
Transport wrapping - Cardboard end protections / bubble paper / cling wrap

MANUFACTURE

Traditional wood fire toasting	Light (L), Medium (M), Medium+ (M+), Heavy (H)
Bung hole	Cauterized - Diameter 48/52
Heads	Blend of oak + stainless steel pins + natural fixations
Watertightness testing	High pressure hot water
Options	Toasted heads Hoops painted black Special laser engraving Spigot hole Wooden or silicone bung

