

Capacity (L.)	400
Stave thickness (mm)	27
Galvanised hoops	8
Chestnut wood hoops	no
Weight (kg)	81
Height (cm)	105
Ø chime (cm)	72
Ø bilge (cm)	88
Interior surface	2,92 m <sup>2</sup>
Riveted hoops	no

## TYPE OF OAK

Quercus Sessilis & Quercus Robur  
Selection and assembly of numerous french sources  
Naturally seasoned in the open air for a minimum of 20 to 24 months  
Checked for the absence of contaminants

## CERTIFICATION/ACCREDITATION

100% PEFC

We are fully committed to the sustainable development of forests and Bureau Veritas certifies our supplies from PEFC forests and unquestioned sourcing. Bureau Veritas certifies that Tonnellerie Bernard respects the criteria for the certification of the control chain (BVFR-PEFC-COC -2172175-G).

## PACKAGING

Unique identification number  
Transport wrapping - Cardboard end protections / bubble paper / cling wrap

## MANUFACTURE

Traditional wood fire toasting	Light (L), Medium (M), Medium+ (M+), Heavy (H)
Bung hole	Cauterized - Diameter 48/52
Heads	Blend of oak + stainless steel pins + natural fixations
Watertightness testing	High pressure hot water
Options	Toasted heads Hoops painted black Special laser engraving Spigot hole Wooden or silicone bung

